

SR-436S (4-Line Wireless PABX Phone System (2.4GHz))



Electrical Specifications	Base Unit	Portable Handset
Frequency	2403-2480 MHz	2403-2480 MHz
channel no.	376	376
Modulation	MSK	MSK
Multiple Access	Frequency Hopping TDMA	Frequency Hopping TDMA
Receiver Sensitivity	<-106 dBm (@BER10-2)	<-106dBm (@BER 10-2)
Range	Open Field : 5 km Urban : 1 km	Open Field : 5 km Urban : 1 km
Telephone Interface	RJ11 x 4	NA
Power Source	AC Adapter	4.8V, 750 mAh NiMH
Charger Current	NA	NA
Regulation Compliance	FCC Part 15, Part 68 CAN/DOC RSS210, Cs03	FCC Part 15, Part 68 CAN/DOC RSS210, CS03 Hearing Aid Compatible
Safety Compliance	CSA 950, UL 1950 FCC SAR	CSA 950, UL 1950 FCC SAR

	(OET-65)	(OET-65)
Electrical Specifications	Base Unit	Portable Handset
Operating Temperature	0~50 oC	-10~50oC
Storage Temperature	-10~70oC	-10~70oC
Humidity	20~70%	20~75%
Dimension without antenna	280 x 215 x 55 mm	150 x 50 x 34 mm
Weight	910 g	230 g